

Package: airportr (via r-universe)

September 15, 2024

Type Package

Title Convenience Tools for Working with Airport Data

Version 0.1.4

Maintainer Dmitry Shkolnik <shkolnikd@gmail.com>

Description Retrieves open source airport data and provides tools to look up information, translate names into codes and vice-verse, as well as some basic calculation functions for measuring distances. Data is licensed under the ODC Open Database License (ODbL).

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports dplyr

Depends R(>= 2.10.0)

URL <https://github.com/dshkol/airportr>

BugReports <https://github.com/dshkol/airportr/issues>

RoxygenNote 7.1.0

Suggests knitr, rmarkdown, testthat, covr

VignetteBuilder knitr

Repository <https://dshkol.r-universe.dev>

RemoteUrl <https://github.com/dshkol/airportr>

RemoteRef HEAD

RemoteSha bec688f399ed8506c14cb806d82eeef56984e656

Contents

airportr	2
airports	2
airports_around	3

airports_near_airport	4
airport_detail	4
airport_distance	5
airport_location	5
airport_lookup	6
city_airports	7

Index	8
--------------	----------

airportr	airportr <i>package</i>
----------	-------------------------

Description

Package to work with airport data

Details

See the README on [GitHub](#)

airports	<i>Table of airport detail data</i>
----------	-------------------------------------

Description

A dataset containing names, codes, locations, altitude, and timezones for airports

Usage

airports

Format

A data frame with 7698 rows and 14 variables:

OpenFlights ID OpenFlights database ID

Name Airport name, sometimes contains name of the city

City Name of city served by airport

IATA 3-letter IATA code

ICAO 4-letter ICAO code

Country Country name as in OpenFlights database. Note that country names may not be ISO 3166-1 standard.

Country Code ISO 3166-1 numeric country code

Country Code (Alpha-2) Name of city served by airport

Country Code (Alpha-3) Name of country where airport is located
Latitude Latitude in decimal degrees
Longitude Longitude in decimal degrees
Altitude Altitude in feet
UTC Hours offset from UTC
DST Daylight savings time. One of E (Europe), A (US/Canada), S (South America), O (Australia), Z (New Zealand), N (None) or U (Unknown)
Timezone Timezone in Olson format
Type Type of airport
Source Source of data. Airport data generally sourced from OurAirports

Source

<https://openflights.org/data.html>

airports_around	<i>Lookup airports near specified coordinates</i>
-----------------	---

Description

A function that returns details of all airports within a user-specified distance of an input coordinate location. Takes as input a longitude and latitude argument.

Usage

```
airports_around(lat, lon, distance = 100)
```

Arguments

lat	Latitude in decimal degrees
lon	Longitude in decimal degrees
distance	Distance boundary for nearest airport lookup in kilometres

Value

A tibble of airports that fall within the specified range of specified location

Examples

```
airports_around(-123, 49.2)

# Or with a user specified distance in kilometres
airports_around(-123, 49.2, distance = 200)
```

airports_near_airport *Lookup airports nearby other airports*

Description

A function that returns details of airports within a user-specified distance of a given airport.

Usage

```
airports_near_airport(input, distance = 100)
```

Arguments

input	An airport name, IATA code, or ICAO code. Input type will be guessed unless explicitly defined
distance	Distance boundary for nearest airport lookup in kilometres

Value

A tibble of airports that fall within the specified range of input airport

Examples

```
airports_near_airport("YVR")

# Or with a user specified distance in kilometres
airports_near_airport("YVR", distance = 200)
```

airport_detail *Lookup full airport details based of a standard airport input*

Description

Return all airport details given an input IATA code, ICAO code, or airport name.

Usage

```
airport_detail(input, input_type)
```

Arguments

input	An airport name, IATA code, or ICAO code. Input type will be guessed unless explicitly defined
input_type	One of "name", "IATA", or "ICAO". Function will attempt to guess type if not supplied

Value

A 1x14 tibble with airport details

Examples

```
airport_detail("YVR")  
airport_detail("London Heathrow Airport")
```

airport_distance	<i>Calculate great circle distance between two airports</i>
------------------	---

Description

A function that calculates distances between pairs of airport codes. Distances are calculated using the Haversine formula which assumes a spherical earth. Distances are returned in kilometres.

Usage

```
airport_distance(airport1, airport2)
```

Arguments

airport1	Takes a three-letter IATA code corresponding to an airport
airport2	As above

Value

The great circle distance in kilometres between the two airports

Examples

```
airport_distance("YVR", "YYZ")
```

airport_location	<i>Lookup airport location coordinates given a standard airport input.</i>
------------------	--

Description

Returns airport location in longitude and latitude coordinates given an input IATA code, ICAO code, or airport name.

Usage

```
airport_location(input, input_type)
```

Arguments

input	An airport name, IATA code, or ICAO code. Input type will be guessed unless #' explicitly defined
input_type	One of "name", "IATA", or "ICAO". Function will attempt to guess type if not supplied

Value

List of longitude and latitude coordinates

Examples

```
airport_location("YVR","IATA")
#' airport_location("Vancouver International Airport","name")
```

airport_lookup	<i>Translate airport codes or names into other standard airport formats</i>
----------------	---

Description

Return city name, airport name, IATA code, or ICAO code given an input IATA code, ICAO code, or airport name.

Usage

```
airport_lookup(input, input_type = "IATA", output_type = "name")
```

Arguments

input	An airport name, IATA code, or ICAO code. Input type will be guessed unless #' explicitly defined
input_type	One of "name", "IATA", or "ICAO". Function will attempt to guess type if not supplied
output_type	One of "name", "city", "IATA", or "ICAO". Defaults to "name" if otherwise not specified

Value

The appropriate city, airport name, IATA code, or ICAO code for that airport

Examples

```
airport_lookup("CYVR")
airport_lookup("YVR", output_type = "city")
airport_lookup("Vancouver International Airport", input_type="name",output_type = "IATA")
airport_lookup("YVR",input_type = "IATA", output_type = "city")

# Produces a list of similar named airports
airport_lookup("Vancouver","name","city")
```

city_airports	<i>Return all airports serving an input city.</i>
---------------	---

Description

This function takes a city normal city name as an input argument and returns all airports associated with that city. Airports are typically associated with their local metropolitan area but some exceptions may be present in the data. If there are no matching results in the data for the city argument, a list of closely named alternatives will be suggested with a warning.

Usage

```
city_airports(city, country)
```

Arguments

city	A city name. If no exact match will attempt to prompt user with suggested alternatives
country	(Optional) A country name or ISO country code in either numeric, alpha-2, or alpha 3 format. Case insensitive.

Value

A Nx17 tibble with airport details where n is the number of airports serving that city

Examples

```
city_airports("Vancouver")
city_airports("London")
city_airports("London", "Canada")
city_airports("London", "CA")
city_airports("London", "CAN")
city_airports("London", "124")
```

Index

* datasets

- airports, [2](#)

- airport_detail, [4](#)
- airport_distance, [5](#)
- airport_location, [5](#)
- airport_lookup, [6](#)
- airportr, [2](#)
- airports, [2](#)
- airports_around, [3](#)
- airports_near_airport, [4](#)

- city_airports, [7](#)